

26"

HIGH VELOCITY FAN galvanized



YM -Yoke Mount (standard)

mounting options:



PS - Pedestal Stroller



CW - Column Wall



PB - Pedestal Base

Shipping Weights:

129 lbs/ 59 kg

115 lbs/ 52 kg

101 lbs/ 46 kg

SIZE	CFM	HP	FAN DIMENSIONS			DISTANCE AIR THROW	SHIPPING WEIGHT
			W	D	I.D.		
26"	7650	1	33"	18.5"	27"	150' / 46 m	93 lbs/ 42 kg

Propeller: 26" Diameter, 3 Blade GalvAlum (18 Degree)
Fan Inlet/Outlet: Galvanized 14 Gauge Spun Steel
Finger Guards: Stainless Steel Spiral
Hand Guards (optional): Galvanized Spiral Wound
RPM: 1800 (1200)
Decibels: 80.8 (75.7) @ 20'

Enclosure: TEAO Standard/ Washdown Available
Frame: 56
Ambient Temperature: 40C
Duty Cycle: Continuous
Power Cord (115V Only): 12' Length
Coverage: 6100 Sq.Ft. Max
Warranty: 2 Years

Voltage	Motor Amps	Running Amps
115V/ 208-230V	13.4/ 6.8-6.7	12.9/ 6.6-6.5
208-230/ 460V*	3.6-3.5/ 1.8	3.4-3.3/ 1.7
277V	5.6	5.4

*standard

26" High Velocity Fan Air Flow Pattern

