

30"

HIGH VELOCITY FAN galvanized




YM -Yoke Mount (standard)

mounting options:



PS - Pedestal Stroller



CW - Column Wall



PB - Pedestal Base

Shipping Weights:

161 lbs/ 73 kg

147 lbs/ 67 kg

136 lbs/ 62 kg

SIZE	CFM	HP	FAN DIMENSIONS			DISTANCE AIR THROW	SHIPPING WEIGHT
			W	D	I.D.		
30"	12,000	1	37"	22"	30 7/8"	200' / 60 m	125 lbs/ 57 kg

Propeller: 30" Diameter, 2 Blade GalvAlum (15 Degree)
Fan Inlet/Outlet: Galvanized 14 Gauge Spun Steel
Finger Guards: Galvanized Spiral
Hand Guards (optional): Galvanized Spiral Wound
RPM: 1800 (1200)
Decibels: 82.2 @ 20'

Enclosure: TEAO
Frame: 56
Ambient Temperature: 40C
Duty Cycle: Continuous
Power Cord (115V Only): 12' Length
Coverage: 12,000 Sq.Ft. Max
Warranty: 2 Years

Voltage	Motor Amps	Running Amps
115V/ 208-230V	13.4/ 6.8-6.7	12.9/ 6.6-6.5
208-230/ 460V*	3.6-3.5/ 1.8	3.4-3.3/ 1.7
277V	5.6	5.4

*standard

