

14"

HIGH VELOCITY FAN



STANDARD YM - YOKE MOUNT

ADDITIONAL MOUNTING OPTIONS:



RM Rack Mount **TC** Truck Cooler **CW** Column-Wall **PS** Portable Stroller **PB** Pedestal Base

SHIPPING WEIGHT:	40 lbs	51 lbs	48 lbs	71 lbs	41 lbs
------------------	--------	--------	--------	--------	--------

SIZE	CFM	HP	FAN DIMENSIONS			AIR THROW DISTANCE	SHIPPING WEIGHT
			W	D	ID		
14"	2600	1/4	20"	16"	14.625"	60'	35 lbs

FEATURES

Propeller: 14" Diameter, 3 Blade GalvAlum, 37°
Fan Inlet/Outlet: High Impact Polypropylene
Finger Guards: OSHA Compliant, Spiral Wound Steel
Power Cord (115V Only): 12' Length (Switch Optional)
RPM: 1725
Decibels: 63.1 @ 20' - 73.1 @ 3'
Coverage: 1800 ft²


Warranty: 2 Years

MOTOR

VOLTAGE	MOTOR AMPS	RUNNING AMPS
115V/208-230V*	2.8/1.4	2.8/1.4
208-230/460V	1.5-1.4/.75	1.4/.70
277V	1.1	1.1

Enclosure: TEAO Standard
Frame: 48
Ambient Temperature: 104°F
Duty Cycle: Continuous

*standard



AIR FLOW PATTERN

Above velocities shown in feet/minute.